

TECHNICAL DATA

PEGACRIL WG 17 GLUE

Pegacril WG17 is a spatulaable glue in mastic form, ideal for gluing Vitroflex Wallguard PC sheets.

CHARACTERISTICS

It has an excellent adhesion on wood, concrete, tiles, metal, etc., as it is a product that polymerizes due to the ambience humidity and the support.

APPLICATION AREAS

Its special formulation makes it to be applied with a serrated spatula, compensating the small inequalities of the substrate.

APPLICATION SYSTEM

We will apply a uniform layer on the wall with serrated spatula and we will put the Vitroflex Wallguard sheet, with a light manual pressure.

We recommend one hour to touch it , its drying depends on the humidity.

The approximate consumption, depending on the support will go from 800 to 1200 g / m2

Security advises:

Do not eat.

S2: Keep out of reach of children

S23: Do not breathe vapors, aerosols.

S24 / 25: Avoid contact with eyes and skin.

S30: Do not mix with water

Industrial product. Professional use

Manufactured in CE.

TECHNICAL SPECIFICATIONS – PEGACRIL WG 17 GLUE

Properties	Value	Unit
Technical data		
Appearance:	viscous paste.	
Color:	oak	
Viscosity:	50000	Mpa.s
Density:	1.30	g / ml
Resistance to rupture:	2	Mpa
Thermal resistance:	-20°C - + 60	°C
Shore A hardness:	50	
Elongation at break:	> 500	%
Setting speed:	2mm / 24h	at 23°Ci 50% RH

The properties described here are typical values of the material. Polimer Tecnic is not responsible for the materials of a specific consignment to exactly match the given values, being able to carry out tests of that heading. The above information is based on our experience and is given in good faith. Due to some installation and processing factors that are beyond our knowledge and control, no guarantee is given regarding such information.